



NOTE
1. Size 40 is out of scope of JIS B 2032.

DIMENSIONS UNIT: mm

SIZE	d	L	H1	H2	H3	D	FLANGE						L1	L2	W	LEVER UNIT	MASS (Kg)	Q'ty
							JIS 5K			JIS 10K								
							C	N	G	C	N	G						
* 40	42	33	40.0	127.5	34.5	79.5	95	4	M12	105	4	M16	35	56	188	L-1A	1.0	
50	50	43	64.5	132.0	34.5	87.0	105	4	M12	120	4	M16	35	56	188	L-1A	1.2	
65	66	46	72.5	140.0	34.5	107.0	130	4	M12	140	4	M16	35	56	188	L-1A	1.4	
80	79	46	84.0	150.0	34.5	122.0	145	4	M16	150	8	M16	35	56	188	L-1B	1.7	
100	101	52	94.0	160.0	34.5	152.0	165	8	M16	175	8	M16	35	56	188	L-1B	2.1	
125	125	56	124.5	195.0	44.0	178.0	200	8	M16	210	8	M20	48	58	260	L-2A	3.7	
150	148	56	136.0	207.0	44.0	208.0	230	8	M16	240	8	M20	48	58	260	L-2A	4.4	

No.	PART	MATERIAL	NOTE
147B	BOTTOM PLATE	EPDM	SIZE 50~150
147A	BOTTOM CAP	SUS304	SIZE 50~150
146	BACK UP RING	ZDC2	SIZE 50~150
145	SPRING WASHER	SUS304	
124	SET SCREW	SUS304	
106	SEAT RUBBER	EPDM	
103	BOTTOM STEM	SUS410	SIZE 50~150
99B	NUT	SUS304	
99A	BOLT	SUS304	
74	THRUST BEARING	PE	
67	BEARING	PPS	
63	BOLT	SUS304	
61	YOKE	SCS13A	
48	SNAP RING	SUS304	
45B	O-RING	EPDM	
45A	O-RING	EPDM	
9	LEVER UNIT		
4	DISC	SCS13A	
3	STEM	SUS410	
1	BODY	ADC12	

FACE TO FACE OR END TO END JIS B2032 SERIES46
 END CONNECTION WAFER TYPE JIS 5K/10K
 WALL THICKNESS MAKER'S STANDARD
 PRESSURE TEST MAKER'S STANDARD

10K ALUMINIUM ALLOY DIE CAST WAFER TYPE RUBBER SEATED BUTTERFLY VALVE WITH LEVER OPERATOR JIS B 2032

APP'D	K.Kobayashi	FIGURE	PRODUCT CODE
CHK'D	H.Fuseya	10ALM-N-LUE	550LA
CHK'D	M.Mochizuki	DRAWING No.	
PREP'D	K.Kohama	16441300	
DATE	JUL.31.'15	MARK	DATE BY

TOYO Toyo Valve Co., Ltd.