



NO	NAME OF PARTS	Q. ty	MATERIAL	SPECIFICATIONS
1	BODY	1	FC 200	
2	STRAINER	1	FC 200	
3	DISC SEAT			
4	DISC	1	FC 200	
5	PLATE	1	SS 400	
6	BOLT&NUT	6	SS 400	M12X50 · 55
7	STUD BOLT	1	SUS304	M8X16
8	PIN	1	SUS304	φ 8mm
9	GASKET PACKIN	1	N B R	t=2mm
10	DISC SEAT PACKIN	1	N B R	t=3mm
11	LEVER	1	FCD450	
12	BOLT&NUT	1	SUS304	M8X50 · 55

HYDROSTATIC TEST PRESSURE  
 VALVE BODY(WATER) . . . 0.980MPa  
 VALVE SEAT(WATER) . . . 0.049MPa  
 OF AUXILIARY COOLING WATER PUMP

(NAME) FOOT VALVE  
 FLANGE STANDARD  
 ALL/FC (10K)

WEIGH	100A=15Kg	125A=20Kg	150A=26Kg
Paint	LACQUER UNDER COAT A Primer		

DATE APPD	Aug. 01. 11	DRAWING NO. 0113
APPD BY	A. Tamaki	
CHKD BY		
DRAWN BY	TAMAKI	

(mm)

SIZE	d	D	t	f	g	h	H1	H2	H3	L	L1	C	n	h	L2	N
100A	100	210	20	2	155	260	170	88	2	244	168	175	8	19	290	8.3
125A	125	250	22	2	185	306	189	115	2	275	186	210	8	23	330	8.3
150A	150	280	22	2	215	318	198	118	2	290	218	240	8	23	350	8.3



TAMAKI IRONWORKS CO., LTD.